

Material Safety Data Sheet

UNIVERSAL FIRE SHIELD FS-700 Fire Stop™ Dated: February 19, 2010

PRODUCT NAME: **UNIVERSAL FIRE SHIELD FS-700 FIRE STOP™**

CHEMICAL FAMILY: Thermal fire and heat resistant type coating compound.

SECTION I - PRODUCT INFORMATION

MANUFACTURER'S NAME:

Unishield International, LLC

3544 Waterfield Pkwy, Lakeland Florida 33803

1. Product Identification

Product Name: FS-700 FIRE STOP™

Use: Area Separation Wall Systems, cabling, electrical and plumbing holes, thermal patch for bulk heads and other uses.

Generic Descriptions: Article composite. FS-700™ consist of a fire resistant type X gypsum compound blended with mold/mildew resistant fiber, fire shield curing agents and volcanic substances. Blended as a liquid putty.

2. Composition/Information on Hazardous Ingredients

TELEPHONE # FOR INFORMATION: 863-667-1805

TRADE SECRET FORMULA

SECTION II - HAZARDOUS COMPONENTS

| COMPONENT | ACGIH | OSHA |
|------------------|-----------------|------------|
| CAS REGISTRY NO. | TLV mg/lm3 | PRL mg/lm3 |
| Gypsum | 10 ^a | 5 |
| 10101-41-4 | | |
| Quartz b | C | 0.1 |
| 14808-60-7 | | |
| Perlite | 10 | 3 |
| 93763-70-3 | | |
| Cellulose | 10 ^a | 5 |
| 9004-34-6 | | |

SECTION III - PHYSICAL PROPERTIES

^b Present as a naturally occurring component of minerals. See Sec. 3 HEALTH

HAZARDS IDENTIFICATION

^c Respirable dust. Use the formula 10 mg/m³

% SiO₂+ 2

Appearance and Odor: A gypsum with organic materials. Composite material provides mildew protection. Surface finish will vary with product, no odor.

3. Health Hazards Identification

• Route(s) of Entry: Inhalation and Dermal

• Potential Health Effects: Skin and eye irritant

Universal Fire Shield FS-700 product does not present an inhalation, ingestion health hazard when using the product. Quartz (crystalline silica) - The International Agency for Research on Cancer (IARC) classifies crystalline silica inhaled in the form of quartz or cristobalite from occupational sources as carcinogenic to humans,

Group 1. The National Toxicology Program (NTP) classifies respirable crystalline silica as a substance, which may be reasonably anticipated to be a carcinogen. OSHA does not regulate crystalline silica as a human carcinogen. Skin Contact: Continued and prolonged contact may result in dry skin. Eye Contact: Direct contact may cause mechanical irritation. Inhalation: Medical Conditions Generally Aggravated by Exposure: Overexposure would generally aggravate respiratory system dysfunctions.

4. First Aid Measures

First Aid Procedures:

- **Eye:** Immediately flush eyes with water for 15 minutes and get medical attention.
- **Skin:** Flush and wash skin with soap and water. Get medical attention if irritation persists.

5. Fire Hazards

- Not Combustible
 - NFPA Hazard Class No: 1/0/0
 - Extinguishing Media: Dry chemical, foam, water fog or spray.
- Special Fire Fighting Procedures: Wear full protective equipment and an approved pressure demand self-contained breathing apparatus (SCBA).

6. Precautions For Safe Handling

- Steps to be taken in Case Material is Released or Spilled: Pickup to avoid tripping hazard.
- Waste Disposal Method: Not a hazardous waste. Dispose of in accordance with applicable federal, state, and local regulations.
- Precautions to be taken in Handling and Storing: Keep dry to preserve usefulness.

7. Stability and Reactivity

- Stability and Reactivity: 1" Universal Fire Shield FS_700™ compound products are stable and hazardous polymerization will not occur. When heated to decomposition, oxides of sulfur and carbon will be released.

8. Exposure Controls/Personal Protection

- Work/Hygiene Practices: The score and snap method of cutting is recommended. Sawing, drilling or machining will produce dust.
- Ventilation: Provide ventilation to maintain a dust level below the PEL/TLV.
- Respiratory Protection: A NIOSH approved respirator for toxic dusts is recommended if the PEL/TLV is exceeded.
- Eye Protection: Safety glasses or goggles.

9. Transport Information

- DOT: Not regulated

Universal Fire Shield FS-700 Dated: February 19, 2010

- 3 -

10. Regulatory Information

EPCRA Section 302 Extremely Hazardous Substance(s) – 40 CFR 355:

No components are listed as EHS under SARA 302.

EPCRA Section 313 Toxic Chemicals List – 40 CFR 372:

Zinc pyrithione (CAS# 13463-41-7) as zinc compounds;

TSCA Section 8b Toxic Chemical Inventory – 40 CFR 721:

All components are listed in the TSCA Inventory.

CERCLA Hazardous Substance(s) – 40 CFR 302.4:

Zinc pyrithione (CAS# 13463-41-7) as zinc compounds

CAA Section 112(b) List of Hazardous Air Pollutants – 40 CFR 63:

No components are listed under CAA HAP list.

CAA Section 112(r) Chemicals for Accidental Release Prevention – 40 CFR 68:

No components are listed under CAA Accidental Release Prevention list.

OSHA Process Safety Management – 29 CFR 1910.119:

No components are listed under OSHA PSM list.

CWA Priority Pollutant List – 40 CFR 401.15:

Zinc pyrithione (CAS# 13463-41-7) as zinc compounds

RCRA Regulated Hazardous Waste – 40 CFR 261.33:

No components are listed RCRA hazardous waste.

11. Other Information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein. This material safety data sheet was prepared to comply with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and with the Workplace Hazardous Materials Information System (WHMIS). This supersedes any previous information.

Disclaimer of Liability:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate, but all statements or suggestions are made without any warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained for the use thereof.